

## IN THE CLAIMS

Please amend the claims to read as follows:

### Listing of Claims

1. (Currently Amended) A network monitoring system that monitors communication between a client and server, the network monitoring system comprising:
  - a data acquisition section that acquires a plurality of packets flown on a network;
  - a data analysis section that acquires action explanation information from the plurality of packets acquired by the data acquisition section;
  - a display-information generation section that generates information of each individual action occurring on the network on the basis of the action explanation information acquired by the data analysis section; and
  - a display unit that displays the information generated by the display-information generation section, wherein:
    - in response to a request by a user, the display-information generation section regenerates, for continuous play back, information of a sequence of individual actions that occurred on the network and cooperates with the display unit to display, during each play back, the regenerated information of each individual action of the sequence at the same time interval within the sequence as the action occurred, ~~and~~
    - action explanation information for explaining each individual action is acquired from a plurality of packets, and

the information displayed by the display unit includes the type of operating system employed by the client, the type of operating system employed by the server, an account name of a user accessing the client, and an icon representing the account name.

2. (Original) The network monitoring system according to claim 1, wherein the action explanation information is defined in advance.

3. (Original) The network monitoring system according to claim 1, wherein the data analysis section identifies kinds of the packets acquired by the data acquisition section and acquires the action explanation information from the packets on the basis of the identified kinds of the packets.

4. (Previously Presented) The network monitoring system according to claim 1, wherein the action explanation information includes:

sending source computer information and destination computer information included in a connection packet;

user information included in an authentication packet;

action object information included in an object specification packet;

action information included in a command packet; and

data included in a data packet.

5. (Previously Presented) The network monitoring system according to claim 1, further comprising:

an analysis data storage section that stores the action explanation information acquired by the data analysis section, wherein:

the display-information generation section regenerates the information of the sequence of individual actions that occurred on the network from the action explanation information stored by the analysis data storage section.

6. (Previously Presented) The network monitoring system according to claim 5, wherein:  
the action explanation information stored by the analysis data storage section includes time information, which corresponds to the time at which the single action occurred; and

the display-information generation section determines the time interval, within the sequence, that each individual action occurred using the time information stored by the analysis data storage section.

7. (Previously Presented) The network monitoring system according to claim 5, wherein the display-information generation section continuously regenerates the sequence after each predetermined period, which period is accurate within 500 milliseconds.

8. (Previously Presented) The network monitoring system according to claim 1, wherein the display-information generation section extracts and generates the information of each action occurring on the network in accordance with a display setting set by a user.

9. (Currently Amended) A network monitoring method for monitoring communication between a client and server, the method comprising:

acquiring a plurality of packets flown on a network;

acquiring action explanation information from the plurality of acquired packets;

generating information of each individual action occurring on the network on the basis of the acquired action explanation information;

regenerating for continuous play back, in response to a request by a user, information of a sequence of individual actions that occurred on the network; and

displaying on a display unit, during each play back, the regenerated information of each individual action of the sequence at the same time interval within the sequence as the action occurred, wherein:

action explanation information for explaining each individual action is acquired from a plurality of packets, and

the information displayed on the display unit includes the type of operating system employed by the client, the type of operating system employed by the server, an account name of a user accessing the client, and an icon representing the account name.

10. (Original) The network monitoring method according to claim 9, wherein the action explanation information is defined in advance.

11. (Original) The network monitoring method according to claim 9, wherein in the acquisition of the action explanation information, kinds of the packets acquired by the packet acquisition are identified and the action explanation information is acquired from the packets on the basis of the identified kinds of the packets.

12. (Previously Presented) The network monitoring method according to claim 9, wherein the action explanation information includes:

    sending source computer information and destination computer information included in a connection packet;

    user information included in an authentication packet;

    action object information included in an object specification packet;

    action information included in a command packet; and

    data included in a data packet.

13. (Previously Presented) The network monitoring method according to claim 9, further comprising:

    storing the acquired action explanation information, wherein:

    the information of the sequence of individual actions that occurred on the network is regenerated from the stored action explanation information.

14. (Previously Presented) The network monitoring method according to claim 13, wherein:

the stored action explanation information includes time information, which corresponds to the time at which the single action occurred; and

the time interval, within the sequence, that each individual action occurred is determined using the stored time information.

15. (Previously Presented) The network monitoring method according to claim 13, further comprising continuously regenerating the sequence after each predetermined period, which period is accurate within 500 milliseconds.

16. (Previously Presented) The network monitoring method according to claim 9, wherein the information of each action occurring on the network is extracted and generated in accordance with a display setting set by a user.

17. (Currently Amended) A network monitoring program recorded on a computer readable medium and executable by a computer, the program making the computer monitor communication between a client and server and perform a process comprising:

acquiring a plurality of packets flown on a network;

acquiring action explanation information from the plurality of acquired packets;

generating information of each individual action occurring on the network on the basis of the acquired action explanation information;

regenerating for continuous play back, in response to a request by a user, information of a sequence of individual actions that occurred on the network; and

displaying on a display unit, during each play back, the regenerated information of each individual action of the sequence at the same time interval within the sequence as the action occurred, wherein

action explanation information for explaining each individual action is acquired from a plurality of packets, and

the information displayed on the display unit includes the type of operating system employed by the client, the type of operating system employed by the server, an account name of a user accessing the client, and an icon representing the account name.

18. (Original) The network monitoring program according to claim 17, wherein the action explanation information is defined in advance.

19. (Original) The network monitoring program according to claim 17, wherein in the acquisition of the action explanation information, kinds of the packets acquired by the packet acquisition are identified and the action explanation information is acquired from the packets on the basis of the identified kinds of the packets.

20. (Previously Presented) The network monitoring program according to claim 17, wherein the action explanation information includes:

sending source computer information and destination computer information included in a connection packet;

user information included in an authentication packet;

action object information included in an object specification packet;

action information included in a command packet; and

data included in a data packet.

21. (Previously Presented) The network monitoring program according to claim 17, wherein:

the process further comprises storing the acquired action explanation information; and

the information of the sequence of individual actions that occurred on the network is regenerated from the stored action explanation information.

22. (Previously Presented) The network monitoring program according to claim 21, wherein:

the stored action explanation information includes time information, which corresponds to the time at which the single action occurred; and

the time interval, within the sequence, that each individual action occurred is determined using the stored time information.

23. (Previously Presented) The network monitoring program according to claim 21, wherein the process further comprises continuously regenerating the sequence after each predetermined period, which period is accurate within 500 milliseconds.



24. (Previously Presented) The network monitoring program according to claim 17, wherein the information of each action occurring on the network is extracted and generated in accordance with a display setting set by a user.

25. (New) The network monitoring system of claim 1, wherein the display unit displays a graphical representation of the communication connection between the client and the server.

26. (New) The network monitoring method of claim 9, wherein the display unit displays a graphical representation of the communication connection between the client and the server.

27. (New) The network monitoring program of claim 17, wherein the display unit displays a graphical representation of the communication connection between the client and the server.